

2

mm 100 008

NPS-53-89-001

NAVAL POSTGRADUATE SCHOOL

Monterey, California

AD-A203 786



DTIC
ELECTE
JAN 23 1989
S H D

SOLUTION OF LINEAR INITIAL VALUE
PROBLEMS ON A HYPERCUBE

Beny Neta

November 1988

Approved for public release; distribution unlimited
Prepared for: Texas Tech University
Lubbock, TX 79409

89 1 23 024


NAVAL POSTGRADUATE SCHOOL
MONTEREY, CALIFORNIA

Rear Admiral R. C. Austin
Superintendent


Harrison Shull
Provost

This report was prepared in conjunction with research conducted for the National Science Foundation and funded through Texas Tech University. Reproduction of all or part of this report is authorized.


Prepared by:


BENY NETA*
Associate Professor of Mathematics

Reviewed by:


HAROLD M. FREDRICKSEN
Chairman
Department of Mathematics

Released by:


KNEALE T. MARSHALL
Dean of Information and
Policy Sciences

*Formerly associated with Texas Tech University

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

1a REPORT SECURITY CLASSIFICATION			1b RESTRICTIVE MARKINGS			
2a SECURITY CLASSIFICATION AUTHORITY			3 DISTRIBUTION/AVAILABILITY OF REPORT			
2b DECLASSIFICATION/DOWNGRADING SCHEDULE			Approved for public release; distribution unlimited			
4 PERFORMING ORGANIZATION REPORT NUMBER(S) NPS-53-89-001			5 MONITORING ORGANIZATION REPORT NUMBER(S) NPS-53-89-001			
6a NAME OF PERFORMING ORGANIZATION Naval Postgraduate School		6b OFFICE SYMBOL (if applicable) 53		7a NAME OF MONITORING ORGANIZATION National Science Foundation		
6c ADDRESS (City, State, and ZIP Code) Monterey, CA 93943				7b ADDRESS (City, State, and ZIP Code) Washington, D.C. 20550		
8a NAME OF FUNDING/SPONSORING ORGANIZATION Texas Technical University		8b OFFICE SYMBOL (if applicable)		9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c ADDRESS (City, State, and ZIP Code) Lubbock, TX 79409				10 SOURCE OF FUNDING NUMBERS		
				PROGRAM ELEMENT NO	PROJECT NO	
				TASK NO.	WORK UNIT ACCESSION NO	
11 TITLE (Include Security Classification) Solution of Linear Initial Value Problems on a Hypercube						
12 PERSONAL AUTHOR(S) Beny Neta and C. P. Katti						
13a TYPE OF REPORT Technical Report		13b TIME COVERED FROM 8/1/86 TO 9/30/88		14 DATE OF REPORT (Year, Month, Day) 1 November 1988		
15 PAGE COUNT 12						
16 SUPPLEMENTARY NOTATION						
17 COSATI CODES			18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)			
FIELD	GROUP	SUB-GROUP	initial value problems, parallel scheme, hypercube, box scheme, recursive doubling technique			
19 ABSTRACT (Continue on reverse if necessary and identify by block number) There are many articles discussing the solution of boundary value problems on various parallel machines. The solution of initial value problems does not lend itself to parallelism, since in this case one uses methods that are sequential in nature. Here we develop a parallel scheme for initial value problems based on the box scheme and a modified recursive doubling technique. Fully implicit Runge Kutta methods were discussed by Jackson and Norsett (1986) and Lie (1987). Lie assumes that each processor of the parallel computer having vector capabilities.						
20 DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS				21 ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED		
22a NAME OF RESPONSIBLE INDIVIDUAL Beny Neta				22b TELEPHONE (Include Area Code) (408) 646-2235		
				22c OFFICE SYMBOL 53Nd		

DD FORM 1473, 84 MAR

83 APR edition may be used until exhausted
All other editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

SOLUTION OF LINEAR INITIAL VALUE PROBLEMS ON A HYPERCUBE

C. P. Katti
Jawaharlal Nehru University
School of Computer and Systems Sciences
New Delhi, 110067
India

and

B. Neta
Naval Postgraduate School
Department of Mathematics
Code 53Nd
Monterey, CA 94943

Abstract

There are many articles discussing the solution of boundary value problems on various parallel machines. The solution of initial value problems does not lend itself to parallelism, since in this case one uses methods that are sequential in nature.

Here we develop a parallel scheme for initial value problems based on the box scheme and a modified recursive doubling technique.

Fully implicit Runge Kutta methods were discussed by Jackson and Norsett (1986) and Lie (1987). Lie assumes that each processor of the parallel computer having vector capabilities.

(12) ←

1 Introduction

We consider the solution of linear initial value problems on a hypercube. "By a hypercube we intend a distributed memory MIMD computer with communication between processors ... via a communication network having the topology of a p -dimensional cube, with the vertices considered as processors and the edges as communication links" (Keller and Nelson, 1987). See also Fox (1984, 1985,

1987) and Fox and Otto (1984). Our method of solution is based on the box scheme to discretize the system of initial value problems

$$y' = Ay + f(x)$$

$$y(a) = y'_0$$

where y and f are n -dimensional vectors and A is an $n \times n$ matrix. The resulting system of equations is solved by a modified version of the recursive doubling technique (see Stone, 1973).

In the next section, the discretization is described and the resulting system of equation is given. Section 3 will describe the modified recursive doubling technique and its application to our system.

It will be interesting to experiment with the method and compare the results to a sequential initial value solver of the same order.

2 The Single Step Method

Consider the system of initial value problems

$$\begin{aligned} y' &= A(x)y + f(x), & a \leq x \leq b \\ y(a) &= y'_0 \end{aligned} \tag{1}$$

where

$$\begin{aligned} y &= (y_1, \dots, y_n)^T, & f &= (f_1(x), \dots, f_n(x))^T, \\ y'_0 &= (y'_{10}, \dots, y'_{n0}), \end{aligned}$$

and

$$A = a_{ij}(x), \quad 1 \leq i, j \leq n.$$

Let

$$x_j = a + jh, \quad j = 0, 1, \dots, m \tag{2}$$

where

$$h = \frac{b-a}{m} \tag{3}$$

be a uniform mesh. The box scheme (see e.g. Keller, 1976), applied to (1) yields

$$\begin{aligned} y_{j+1} &= y_j + h \left\{ A_{j+\frac{1}{2}} (y_{j+1} + y_j) / 2 + f_{j+\frac{1}{2}} \right\}, \\ y_0 &= y'_0 \end{aligned} \quad (4)$$

where

$$\begin{aligned} A_{j+\frac{1}{2}} &= A \left(a + \left(j + \frac{1}{2} \right) h \right) \\ f_{j+\frac{1}{2}} &= f \left(a + \left(j + \frac{1}{2} \right) h \right) \end{aligned}$$

and y_j is the approximation to $y(x_j)$.

Let $\{j_i, i = 1, 2, \dots, s\}$ be a strictly increasing sequence such that $j_1 > 0$ and $j_s = m$. We shall compute the solution at the points $x_i = x_{j_i}$. Let Φ_i be $n \times n$ matrices defined for each i

$$\Phi_i = \prod_{j=j_{i-1}}^{j_i-1} \left(I - \frac{h}{2} A_{j+\frac{1}{2}} \right)^{-1} \left(I + \frac{h}{2} A_{j+\frac{1}{2}} \right), \quad i = 1, 2, \dots, s, \quad (5)$$

where $j_0 = 0$ and h is sufficiently small so that $I - \frac{h}{2} A_{j+\frac{1}{2}}$ are nonsingular.

Similarly let the n -vector φ_i be

$$\begin{aligned} \varphi_i &= \left(I - \frac{h}{2} A_{j_i-\frac{1}{2}} \right)^{-1} \left(I + \frac{h}{2} A_{j_i-\frac{1}{2}} \right) \tilde{y}_{j_i-1-j_{i-1}} \\ &\quad + h \left(I - \frac{h}{2} A_{j_i-\frac{1}{2}} \right)^{-1} f_{j_i-\frac{1}{2}}, \quad i = 1, 2, \dots, s, \end{aligned} \quad (6)$$

where

$$\tilde{y}_0 = 0 \quad (7)$$

and

$$\begin{aligned} \tilde{y}_{j+1} &= \left(I - \frac{h}{2} A_{j+\frac{1}{2}+j_{i-1}} \right)^{-1} \left[\left(I + \frac{h}{2} A_{j+\frac{1}{2}+j_{i-1}} \right) \tilde{y}_j + h f_{j+\frac{1}{2}+j_{i-1}} \right] \\ j &= 0, \dots, j_i - j_{i-1} - 2. \end{aligned} \quad (8)$$

Then it can be easily shown as in Keller and Nelson (1987), that

$$Y_{j_i} = \Phi_i y_{j_{i-1}} + \varphi_i, \quad i = 1, 2, \dots, s. \quad (9)$$



Distribution For	
PR&I	<input checked="" type="checkbox"/>
AD	<input type="checkbox"/>
AS	<input type="checkbox"/>
Distribution	
Distribution/	
Availability Codes	
Full and/or	
Dist	Dist
A-1	

Remarks

1. The matrices to be inverted are of order n , the number of equations in the original system (1).
2. The last factor in the product defining Φ_i is the matrix required in computing φ_i .
3. The vector $\tilde{y}_{j_i-1-j_{i-1}}$ can be computed by (7) - (8) in the same loop one computes Φ_i since it requires the same matrices.

3 Parallel Evaluation

To solve (9) on a hypercube with $p = s$ processors, one can modify the recursive doubling technique developed by Stone (1973).

Let

$$\begin{aligned} b_1 &= \Phi_1 y'_0 + \varphi_1 \\ b_j &= \varphi_j, \quad j = 2, 3, \dots, s \end{aligned} \quad (10)$$

and let $Y_i(j)$ be a function of $b_j, b_{j-1}, \dots, b_{j-i+1}, \Phi_j, \dots, \Phi_{j-i+1}$. Then the following results can be proved using similar arguments as in Stone(1973).

Theorem. Let $Y_i(j)$ satisfy the recurrence relation

$$Y_{i+1}(j) = Y_1(j) + \Phi_j Y_i(j-1), \quad i, j \geq 1 \quad (11)$$

with boundary conditions

$$\begin{aligned} Y_1(j) &= b_j, \quad j \geq 1 \\ Y_i(j) &= 0, \quad j \leq 0 \text{ or } i \leq 0. \end{aligned} \quad (12)$$

Then

(i)

$$Y_{i+s}(j) = Y_s(j) + \prod_{k=j-s+1}^j \Phi_{2j-k-s+1} Y_i(j-s) \quad (13)$$

(ii)

$$Y_i(j) = \sum_{k=1}^j \left\{ \prod_{s=k+1}^j \Phi_{j-s+k+1} \right\} Y_1(k), \quad i \geq j \geq 1, \quad (14)$$

(iii) for

$$i \geq j \geq 1, \quad Y_i(j) = y_{ji}. \quad (15)$$

Corollary

$$Y_{2i}(j) = Y_i(j) + \left\{ \prod_{k=j-i+1}^j \Phi_{2j-k-i+1} \right\} Y_i(j-i), \quad i, j \geq 1 \quad (16)$$

This corollary provides the recursive doubling algorithm for the solution of (9). Let

$$M_i(j) = \begin{cases} \prod_{k=1}^j \Phi_{j-k+1} & j \leq i \\ \prod_{k=j-i+1}^j \Phi_{2j-k+1-i}, & j \geq i \end{cases} \quad (17)$$

then (16) can be written as

$$\begin{aligned} Y_{2i}(j) &= Y_i(j) + M_i(j)Y_i(j-i) \quad i, j \geq 1 \\ M_{2i}(j) &= M_i(j)M_i(j-i) \quad i, j \geq 1 \end{aligned} \quad (18)$$

with boundary conditions

$$\begin{aligned} M_1(j) &= \Phi_j, \quad j \geq 1 \\ M_1(j) &= I, \quad i \leq 0 \text{ or } j \leq 0. \end{aligned} \quad (19)$$

We are now ready to state the algorithm.

Algorithm

For $i = 1$ to $s/2$ in steps of i do:

$$\begin{aligned} Y_{2i}(j) &= Y_i(j) + M_i(j)Y_i(j-i) \quad i \leq j \leq s \\ M_{2i}(j) &= M_i(j)M_i(j-i) \quad i \leq j \leq s \end{aligned}$$

Next i .

From our theorem, $Y_s(j) = y_{j_s}$ for $1 \leq j \leq s$, so that $Y s$ is the solution of (9). We note that for each i , the indices pertaining to j are executed simultaneously on s processors. Since i doubles during each iteration, $\log_2 s$ iterations are required for computation.

Acknowledgements

This work was partially supported by the National Science Foundation, through Grants No. INT-8519159 and INT-8613396.

References

1. H.B. Keller and P. Nelson (1987). *Hypercube Implementations of Parallel Shooting*, **Applied Mathematics and Computations**, to appear.
2. G. Fox (1984). *Concurrent Processing for Scientific Calculations*, Proceedings COMPCON 1984 Conference. pp.70-73, IEEE Computer Society.
3. G.C. Fox (1984). *Are Concurrent Processors General Purpose Computers?*, **IEEE Trans. Nucl. Sci.** NS-32, pp.182-186.
4. G.C. Fox and S. W. Otto (1984). *Algorithm for Concurrent Processors*, **Physics Today**, 37, No. 5, pp.50-59.
5. H.S. Stone (1973). *An Efficient Parallel Algorithm for the Solution of a Tridiagonal Linear System of Equations*, **J. Assoc. Comput. Mach.**, 20, pp. 27-38.
6. H. B. Keller (1976). *Numerical Solution of Two Point Boundary Value Problems*, **SIAM, Reg. Conf. Ser. in Applied Math.**
7. K. K. Jackson and S. P. Norsett (1986). *Parallel Runge-Kutta Methods*, unpublished report.

8. I. Lie (1987). *Some Aspects of Parallel Runge-Kutta Methods*, **Institutt for Numerisk Matematikk**, Universitetet i Trondheim, Norway, ISBN 82-7151-068-1, 39 pages.

DISTRIBUTION LIST

	NO. OF COPIES
Director Defense Tech. Information Center Cameron Station Alexandria, VA 22314	2
Director of Research Administration Code 012 Naval Postgraduate School Monterey, CA 93943	1
Library Code 0142 Naval Postgraduate School Monterey, CA 93943	2
Department of Mathematics Code 53 Naval Postgraduate School Monterey, CA 93943	1
Center for Naval Analyses 4401 Ford Avenue Alexandria, VA 22302-0268	1
Professor Beny Neta Code 53Nd Department of Mathematics Naval Postgraduate School Monterey, CA 93943	15
Dr. C. P. Katti J. Nehru University School of Computer & Systems Sciences New Delhi 110067 India	5
Professor Paul Nelson Texas A & M University Department of Nuclear Engineering and Mathematics College Station, TX 77843-3133	1
Professor H. B. Keller Department of Applied Mathematics California Institute of Technology Pasadena, CA 91125	1

Professor H. Dean Victory, Jr. Texas Tech University Department of Mathematics Lubbock, TX 79409	1
Professor Gordon Latta Code 53Lz Department of Mathematics Naval Postgraduate School Monterey, CA 93943	1
Professor Allan Goldstein Code 53Go Department of Mathematics Naval Postgraduate School Monterey, CA 93943	1
Professor Arthur Schcenstadt Code 53Zh Department of Mathematics Naval Postgraduate School Monterey, CA 93943	1
Professor M. M. Chawla, Head Department of Mathematics III/III/B-1, IIT Campus Hauz Khas, New Delhi 110016 India	1